

ICS 59.080.30

CCS W 71

FZ

中华人民共和国纺织行业标准

FZ/T ×××××-××××

棉多层印染布

Printed and dyed cotton multilayer fabric

()

××××-××-××发布

××××-××-××实施

中华人民共和国工业和信息化部 发布
中国标准出版社 出版

前 言

GB/T 1.1-2020

1

SAC/TC 209/SC 11

棉多层印染布

1 范围

2 规范性引用文件

GB/T 250					
GB/T 411					
GB/T 3917.2	2				()
GB/T 3920					
GB/T 3921-2019					
GB/T 3922-2013					
GB/T 3923.1	1				()
GB/T 4666					
GB/T 4668					
GB/T 4669-2008					
GB/T 4802.1-2008				1	
GB/T 4841.3	2/1	1/3	1/6	1/12	1/25
GB/T 5296.4	4				
GB/T 5453-1997					
GB/T 8170					
GB/T 8427-2019					
GB/T 8628					
GB/T 8629-2017					
GB/T 8630					
GB/T 14801					
GB/T 17760					
GB 18401					
GB/T 21655.1-2008				1	
GB 31701					
FZ/T 10005					
FZ/T 10010					

3 术语和定义

GB/T 411

FZ/T xxxx-xxxx

3.1

棉多层印染布 **printed and dyed cotton multilayer fabric**

4 分类

5 要求

5.1 项目

5.2 分等规定

5.2.1

5.2.2

5.2.3

5.3 内在质量

5.3.1 GB 18401 GB 31701

5.3.2 1

表1 内在质量评等规定

/%			-3.0 +3.0	-4.0 +4.0
			-2.0 +2.0	-3.0 +3.0
/ %			-5.0 +5.0	
/N	200g/m ²		600	
			350	
	150g/m ² 200g/m ²		350	
			250	
	150g/m ² 200g/m ²		250	
			200	
/N	200g/m ²		17.0	
			15.0	
	150g/m ²		13.0	

	200g/m ²		11.0		
	150g/m ²		7.0		
	200g/m ²		6.7		
/ %			-3.0 +1.0	-5.0 +1.5	-7.0 +2.0
			-3.0 +1.0	-5.0 +1.5	-7.0 +2.0
/			4	3	
/ mm/s			1500	1000	800
/s			5.0	10.0	20.0
/			4	3	3
			4	3-4	3
			3-4	3-4	3
		a b	4	3-4	3
			3	3	2-3
			3-4	3	3
			3-4	3	3
			4	4	3-4
注 1:		100 g/m ²			
注 2:					
a					
b	GB/T 4841.3		1/12		1/12

5.4 外观质量

5.4.1 外观质量要

2

表 2 外观质量评等规定

/cm	140 cm		-1.0 +2.0	-1.5 +2.5	-2.0 +3.0
	140 cm	240 cm	-1.5 +2.5	-2.0 +3.0	-2.5 +3.5
	240 cm		-2.5 +3.5	-3.0 +4.0	-3.5 +4.5
/			4	4	3-4
			4	3-4	3
			4	3-4	3
			4	3-4	3
		*		4-5	4

		4	3-4	3
		4	3-4	3
$b/\%$		2.5	3.5	5.0
		2.0	3.0	4.5
	/ /100 m ²	18	28	40
注 1: 注 2:				
a	240 cm			
b		240 cm		0.5%

5.4.2 每匹（段）布的局部性疵点允许总评分

$$A \frac{a \times L \times W}{100} \dots\dots\dots 1$$

1 GB/T 8170

A ——
a —— /100 m²
L —— m
W —— m

5.4.3 假开剪和拼件的规定

- 5.4.3.1
- 5.4.3.2 4 3
- 5.4.3.3 10 m 60 m 5 30 m
2 30 m
- 5.4.3.4 1 20 10
- 5.4.3.5

6 试验和检验方法

6.1 GB/T 4668
2 GB/T 8170

$$e_{j.w} = \frac{D_1 - D_{j.w}}{D_{j.w}} \times 100\% \dots\dots\dots 2$$

$e_{j.w}$ ——
 $D_{j.w}$ —— , /10 cm
 D_1 —— /10 cm

6.2 GB/T 4669-2008 6 3
GB/T 8170

$$G = \frac{m_1 - m}{m} \times 100\% \dots\dots\dots 3$$

G ——

m ——

m_l ——

g/m^2

g/m^2

注:

6.3		GB/T 3923.1			
6.4		GB/T 3917.2			
6.5		GB/T 8628	GB/T 8629-2017	A	4 N
	A	GB/T 8630			
6.6		GB/T 4802.1-2008		490 cN	0
50					
6.7		GB/T 5453-1997		100Pa,	20cm ²
6.8		GB/T 21655.1-2008	8.2		
6.9		GB/T 8427-2019	3		
6.10		GB/T 3921-2019	C 1		
6.11		GB/T 3920			
6.12		GB/T 3922-2013			
6.13		GB/T 4666			
6.14		GB/T 250			
6.15				GB/T 14801	
6.16			GB/T 17760		

7 检验规则

FZ/T 10005

8 标志与包装

FZ/T 10010

GB/T 5296.4

9 其它

